

## INDUSTRIAL COMPONENT DATA

**T0-3-15069/I1 222639 Y7-222639 EATON ELECTRIC Step switches, Contacts: 6, 20 A, front plate: 0-2, 45 °, main..**

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15069/I1



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-3-15069/I1   |
| Catalog number  | Y7-222639       |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-2708ED0F01   |
| Generated       | 2026-08-05      |

**Product Overview**

Step switches, Contacts: 6, 20 A, front plate: 0-2, 45 °, maintained, surface mounting

T0-3-15069/I1

Eaton Moeller® series T0 Step switches, T0, 20 A, surface mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, With 0 (Off) position, 0-2, Design number 15069

Step switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

**Additional Product Information**

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 222639 Model Code T0-3-15069/I1 EAN

4015082226398 Product Length/Depth 137 mm Product Height 122 mm Product Width 80 mm Product Weight 0.288 kg

Certifications IEC/EN 60947

IEC/EN 60204

IEC/EN 60947-3

VDE 0660 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 222639 Low-voltage industrial controls and switchgear (EC001105)

Feature Name  
Feature Value  
Model (EF000010)  
Reverser  
Number of poles (EF001391)  
3  
With zero (off) position (EF001416)  
Yes  
With retraction in 0-position (EF002428)  
No  
Rated permanent current  $I_u$  (EF001389)  
20 A  
Rated operation current  $I_e$  at AC-3, 400 V (EF001392)  
11.5 A  
Rated operation power at AC-3, 400 V (EF001364)  
4 kW  
Degree of protection (IP), front side (EF003118)  
IP65  
Degree of protection (NEMA), front side (EF011961)  
12  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Suitable for floor mounting (EF007243)  
Yes  
Suitable for front mounting (EF007246)  
No  
Suitable for distribution board installation (EF007262)  
No  
Suitable for intermediate mounting (EF007264)  
No  
Complete device in housing (EF007317)  
Yes  
Housing material (EF001596)  
Plastic  
Type of control element (EF006976)  
Short thumb-grip  
Type of electrical connection of main circuit (EF006819)  
Screw connection

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15069/I1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.