

INDUSTRIAL COMPONENT DATA

T0-3-151/I1 222640 Y7-222640 EATON ELECTRIC Step switches, Contacts: 6, 20 A, front plate: 1-6, 45 °, mainta..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-151/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-151/I1
Catalog number	Y7-222640
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-FE85FC07CD
Generated	2026-08-05

Product Overview

Step switches, Contacts: 6, 20 A, front plate: 1-6, 45 °, maintained, surface mounting

T0-3-151/I1

Step switches, T0, 20 A, surface mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, Without 0 (Off) position, 1-6, Design number 151

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 3 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 1-6

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Step switches, T0, 20 A, surface mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, Without 0 (Off) position, 1-6,

Design number 151Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate,

Contacts: 6, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance:

maintained, Without 0 (Off) position, 3 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 1-6

General specificationsProduct nameEaton Moeller® series T0 Step switchPart no.T0-3-151/I1EAN4015082226404Product

Length/Depth137 millimetreProduct height122 millimetreProduct width80 millimetreProduct weight0.288

kilogramCertificationsVDE 0660

IEC/EN 60204

IEC/EN 60947

IEC/EN 60947-3Product TradenameT0Product TypeStep switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFeaturesComplete device in housingFitted with:Black thumb grip and front plateInscription1-6Number of polesSingle-poleGeneral informationDegree of protectionIP65Degree of protection (front side)IP65

NEMA 12Lifespan, mechanical400,000 OperationsMounting methodSurface mountingMounting positionAs requiredNumber of contact units3Operating frequency1200 Operations/hOvervoltage categoryIIIPollution degree3Product categoryControl switchesRated impulse withstand voltage (Uimp)6000 V A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-151/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.