

INDUSTRIAL COMPONENT DATA

T0-3-15122/E 012929 Y7-12929 EATON ELECTRIC Auxiliary winding switch, Contacts: 6, 20 A, front plate: 2-STAR..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15122/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15122/E
Catalog number	Y7-12929
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-30233E93F9
Generated	2026-08-04

Product Overview

Auxiliary winding switch, Contacts: 6, 20 A, front plate: 2-START>0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 3 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0

Switch auxiliary winding; 6-pole; 20a; rating Plate: 2-START>0

Eaton Moeller® series T0 Auxiliary winding switch, T0, 20 A, flush mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, With 0 (Off) position, with spring-return from both directions to 0, 2-START>0

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Auxiliary winding switch Catalog Number 012929 Model Code T0-3-15122/E EAN 4015080129295 Product Length/Depth 95 mm Product Height 48 mm Product Width 48 mm Product Weight 0.127 kg

Certifications VDE 0660

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

IEC/EN 60947-3

CSA Class No.: 3211-05

CSA

UL File No.: E36332

IEC/EN 60204

UL Category Control No.: NLRV

CSA-C22.2 No. 94

UL

CSA File No.: 012528

CE

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 012929 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15122/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.