

INDUSTRIAL COMPONENT DATA

T0-3-15123/IVS 012938 Y7-12938 EATON ELECTRIC Auxiliary winding switch, Contacts: 6, 20 A, front plate: STAR..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15123/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15123/IVS
Catalog number	Y7-12938
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-87D94D4714
Generated	2026-08-06

Product Overview

Auxiliary winding switch, Contacts: 6, 20 A, front plate: START>2-0-1

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, with spring-return from both directions, 3 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: START>2-0-1

Switch auxiliary winding; 6-pole; 20a; rating Plate: START>2-0-1

Auxiliary winding switch, T0, 20 A, service distribution board mounting, 3 contact unit(s), Contacts: 6, 45 °, momentary/maintained, START>2-0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Auxiliary winding switch Catalog Number 012938 Model Code T0-3-15123/IVS
EAN 4015080129387 Product Length/Depth 101 mm Product Height 55 mm Product Width 54 mm Product Weight 0.155 kg

Certifications UL 60947-4-1

UL Category Control No.: NLRV

VDE 0660

CSA Class No.: 3211-05

UL File No.: E36332

CSA

CSA File No.: 012528

CSA-C22.2 No. 94

CE

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

IEC/EN 60947

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 012938 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

4

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15123/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.