

**INDUSTRIAL COMPONENT DATA**

# T0-3-15259/E 012985 Y7-12985 EATON ELECTRIC On-Off switch, 3 pole + 2 N/O, 20 A, 90 °, flush mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15259/E



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | T0-3-15259/E        |
| Catalog number  | Y7-12985            |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-8B54C15527       |
| Generated       | 2026-08-05          |

## Product Overview

On-Off switch, 3 pole + 2 N/O, 20 A, 90 °, flush mounting

Disconnect switch ON-OFF; 3-pole + 2 NO; 20 A; 90 °; Mounting

Eaton Moeller® series T0 On-Off switch, T0, 20 A, flush mounting, 3 contact unit(s), 3 pole, 2 N/O, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: T0, with black thumb grip and front plate, 3 pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, front plate:

0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s),

Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

## Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 On-off switch Catalog Number 012985 Model Code T0-3-15259/E EAN

4015080129851 Product Length/Depth 95 mm Product Height 48 mm Product Width 48 mm Product Weight 0.127 kg

Certifications VDE 0660

CSA Class No.: 3211-05

UL 60947-4-1

UL File No.: E36332

CSA-C22.2 No. 94

IEC/EN 60947-3

CE

UL Category Control No.: NLRV

IEC/EN 60947

CSA

CSA-C22.2 No. 60947-4-1-14

UL

CSA File No.: 012528

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 012985 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage U<sub>e</sub> AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current I<sub>u</sub> (EF001389)

20 A

Rated permanent current at AC-21, 400 V (EF009165)

20 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Rated short-time withstand current I<sub>cw</sub> (EF007050)

0.32 kA

Rated operation power at AC-23, 400 V (EF007027)

5.5 kW

Switching power at 400 V (EF009166)

5.5 kW

Conditioned rated short-circuit current I<sub>q</sub> (EF001444)

6 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15259/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.