

INDUSTRIAL COMPONENT DATA

T0-3-15683/I2H/MBS/SVB-SW 182434 Y7-182434 EATON ELECTRIC Main switch, 3p+2S+1Ö,20A,controlled stop function..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15683/I2H/MBS/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15683/I2H/MBS/SVB-SW
Catalog number	Y7-182434
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-8C6572B3A8
Generated	2026-08-03

Product Overview

Main switch, 3p+2S+1Ö,20A,controlled stop function,90 °,lockable in the 0 (Off) position,surface mount.,hard knockout version,with mounting plate scr.

T0-3-15683/I2H/MBS/SVB-SW

Main switch, T0, 20 A, surface mounting, 3 contact unit(s), 3 pole, 2 N/O, 1 N/C, STOP function, Lockable in the 0 (Off) position, hard knockout version, with assembly sheet screen

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: STOP function, With black rotary handle and locking ring, Notes: hard knockout version, with assembly sheet screen, 3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, T0, 20 A, surface mounting, 3 contact unit(s), 3 pole, 2 N/O, 1 N/C, STOP function, Lockable in the 0 (Off) position, hard knockout version, with assembly sheet screenMain switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: STOP function, With black rotary handle and locking ring, Notes: hard knockout version, with assembly sheet screen, 3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of

Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW,
Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,
Switch-disconnector according to IEC/EN 60947-3 Delivery program

Product range Main switch

maintenance switch

Repair switch Part group reference T0 Stop Function STOP function With black rotary handle and locking ring Notes hard
knockout version

with assembly sheet screen Number of poles 3 pole Auxiliary contacts 2 N/O 1 N/C Locking facility Lockable in the 0 (Off)
position Degree of Protection IP65 Design surface mounting Contact sequence Switching angle 90 ° Function Motor rating
AC-23A, 50 - 60 Hz [P] 400 V [P] 5.5 kW Rated uninterrupted current [I_u] 20 A Note on rated uninterrupted current ! I_u Rated
uninterrupted current I_{uis} specified for max. cross-section. Number of contact units 3 contact unit(s) Technical data
General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 609...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15683/I2H/MBS/SVB-SW with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.