

## INDUSTRIAL COMPONENT DATA

# T0-3-15683/I2H/MBS/SVB-SW 182434 Y7-182434 EATON ELECTRIC Main switch, 3p+2S+1Ö,20A,controlled stop function..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15683/I2H/MBS/SVB-SW



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | EATON - MOELLER           |
| MPN / Reference | T0-3-15683/I2H/MBS/SVB-SW |
| Catalog number  | Y7-182434                 |
| Category        | Switch disconnecter       |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-8C6572B3A8             |
| Generated       | 2026-08-05                |

## Product Overview

Main switch, 3p+2S+1Ö,20A,controlled stop function,90 °,lockable in the 0 (Off) position,surface mount.,hard knockout version,with mounting plate scr.

T0-3-15683/I2H/MBS/SVB-SW

Main switch, T0, 20 A, surface mounting, 3 contact unit(s), 3 pole, 2 N/O, 1 N/C, STOP function, Lockable in the 0 (Off) position, hard knockout version, with assembly sheet screen

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: STOP function, With black rotary handle and locking ring, Notes: hard knockout version, with assembly sheet screen, 3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

Main switch, T0, 20 A, surface mounting, 3 contact unit(s), 3 pole, 2 N/O, 1 N/C, STOP function, Lockable in the 0 (Off) position, hard knockout version, with assembly sheet screenMain switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: STOP function, With black rotary handle and locking ring, Notes: hard knockout version, with assembly sheet screen, 3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of

Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW,  
Rated uninterrupted current: I<sub>u</sub> = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,  
Switch-disconnector according to IEC/EN 60947-3 Delivery program

Product range Main switch

maintenance switch

Repair switch Part group reference T0 Stop Function STOP function With black rotary handle and locking ring Notes

hard knockout version

with assembly sheet screen Number of poles 3 pole Auxiliary contacts 2 N/O 1 N/C Locking facility Lockable in the 0 (Off)

position Degree of Protection IP65 Design surface mounting Contact sequence Switching angle 90 ° Function Motor rating

AC-23A, 50 - 60 Hz [P] 400 V [P] 5.5 kW Rated uninterrupted current [I<sub>u</sub>] 20 A Note on rated uninterrupted current ! I<sub>u</sub> Rated

uninterrupted current I<sub>uis</sub> specified for max. cross-section. Number of contact units 3 contact unit(s) Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 609...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15683/I2H/MBS/SVB-SW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.