

INDUSTRIAL COMPONENT DATA

T0-4-106/IVS 013519 Y7-13519 EATON ELECTRIC Multi-speed switches, Contacts: 7, 20A, 2 speeds, 2 separate windin..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-106/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-106/IVS
Catalog number	Y7-13519
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F846E69860
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 7, 20A, 2 speeds, 2 separate windings, front plate: 2-0-1, 60 °, maintained, service distribution board mounting, SOND 30

Switch Multi-speed; 7-pole; 20; 2 speeds; 2 separate windings; rating Plate: 2-0-1; 60 °; Interlock; Mounting in distribution cabinet; SOND 30

Eaton Moeller® series T0 Multi-speed switches, T0, 20 A, service distribution board mounting, 4 contact unit(s), Contacts: 7, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 30, Design number 106

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 30, Contacts: 7, Degree of Protection: Front IP30, Design: service distribution board mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 013519 Model Code T0-4-106/IVS EAN 4015080135197 Product Length/Depth 111 mm Product Height 55 mm Product Width 54 mm Product Weight 0.179 kg

Certifications CSA File No.: 012528

CSA-C22.2 No. 94

UL 60947-4-1

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

UL

VDE 0660

CSA

IEC/EN 60947

IEC/EN 60204

IEC/EN 60947-3

UL Category Control No.: NLRV

CE

CSA Class No.: 3211-05 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 013519 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-106/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.