

**INDUSTRIAL COMPONENT DATA**

# T0-4-131/E 013529 Y7-13529 EATON ELECTRIC Reversing switches, Contacts: 7, 20 A, front plate: 2-0-1, 45 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-131/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-4-131/E      |
| Catalog number  | Y7-13529        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-95ECA88F77   |
| Generated       | 2026-08-06      |

## Product Overview

Reversing switches, Contacts: 7, 20 A, front plate: 2-0-1, 45 °, maintained, flush mounting, SOND 28

Reversing switch; 7-pole; 20a; rating Plate: 2-0-1; 45 °; Interlock; recessed Mounting; SOND 28

Eaton Moeller® series T0 Reversing switches, T0, 20 A, flush mounting, 4 contact unit(s), Contacts: 7, 45 °, maintained, With 0 (Off) position, 2-0-1, SOND 28, Design number 131

Reversing switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 28, Contacts: 7, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

## Additional Product Information

**General specifications**

Product Name Eaton Moeller® series T0 Reversing switch Catalog Number 013529 Model Code T0-4-131/E EAN 4015080135296 Product Length/Depth 105 mm Product Height 48 mm Product Width 48 mm Product Weight 0.156 kg

Certifications CSA Class No.: 3211-05

CSA

CSA File No.: 012528

UL Category Control No.: NLRV

CE  
CSA-C22.2 No. 94  
IEC/EN 60947-3  
UL File No.: E36332  
UL 60947-4-1  
VDE 0660  
IEC/EN 60204  
IEC/EN 60947  
CSA-C22.2 No. 60947-4-1-14  
UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second  
ETIM for 013529 Low-voltage industrial controls and switchgear (EC001105)  
Feature Name  
Feature Value  
Model (EF000010)  
Reversing switch  
Number of poles (EF001391)  
3  
With zero (off) position (EF001416)  
Yes  
With retraction in 0-position (EF002428)  
No  
Rated permanent current Iu (EF001389)  
20 A  
Rated operation current Ie at AC-3, 400 V (EF001392)  
11.5 A  
Rated operation power at AC-3, 400 V (EF001364)  
4 kW  
Degree of protection (IP), front side (EF003118)  
IP65  
Degree of protection (NEMA), front side (EF011961)  
12  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Suitable for floor mounting (EF007243)  
No  
Suitable for front mounting (EF007246)  
Yes  
Suitable for distribution board installation (EF007262)  
No  
Suitable for intermediate mounting (EF007264)  
No  
Complete device in housing (EF007317)  
No

Housing materia...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-131/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.