

INDUSTRIAL COMPONENT DATA

T0-4-15007/EZ 013558 Y7-13558 EATON ELECTRIC Step switches, Contacts: 7, 20 A, front plate: 1-7, 45 °, Unint..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-15007/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-15007/EZ
Catalog number	Y7-13558
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-1139EE0A38
Generated	2026-08-06

Product Overview

Step switches, Contacts: 7, 20 A, front plate: 1-7, 45 °, Uninterruptible, maintained, centre mounting

Switch steps; 7-pole; 20a; rating Plate: 1-7; 45 °; Uninterruptible power supply; Interlock; recessed Mounting with central fixing

Eaton Moeller® series T0 Step switches, T0, 20 A, centre mounting, 4 contact unit(s), Contacts: 7, 45 °, maintained, Without 0 (Off) position, 1-7, Design number 15007

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 7, Contact behavior: Uninterruptible, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 4 contact unit(s), Rated uninterrupted current: I_u = 20 A, front plate: 1-7

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 013558 Model Code T0-4-15007/EZ EAN 4015080135586 Product Length/Depth 125 mm Product Height 48 mm Product Width 48 mm Product Weight 0.177 kg
Certifications UL Category Control No.: NLRV
CSA-C22.2 No. 60947-4-1-14
UL 60947-4-1

CSA

IEC/EN 60947-3

CE

CSA Class No.: 3211-05

IEC/EN 60947

CSA-C22.2 No. 94

IEC/EN 60204

VDE 0660

UL

UL File No.: E36332

CSA File No.: 012528 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 013558 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

7

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-15007/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.