

INDUSTRIAL COMPONENT DATA

T0-4-15126/E 013635 Y7-13635 EATON ELECTRIC Auxiliary winding switch, Contacts: 8, 20 A, front plate: 2-STAR..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-15126/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-15126/E
Catalog number	Y7-13635
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-43B1D6B73E
Generated	2026-08-04

Product Overview

Auxiliary winding switch, Contacts: 8, 20 A, front plate: 2-START>0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 4 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0

Switch auxiliary winding; 8-pole; 20a; rating Plate: 2-START>0

Eaton Moeller® series T0 Auxiliary winding switch, T0, 20 A, flush mounting, 4 contact unit(s), Contacts: 8, 45 °, maintained, With 0 (Off) position, with spring-return from both directions to 0, 2-START>0

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Auxiliary winding switch Catalog Number 013635 Model Code T0-4-15126/E EAN 4015080136354 Product Length/Depth 105 mm Product Height 48 mm Product Width 48 mm Product Weight 0.156 kg

Certifications IEC/EN 60947

CSA Class No.: 3211-05

CSA-C22.2 No. 94

UL 60947-4-1

UL Category Control No.: NLRV

CSA

UL File No.: E36332

CSA File No.: 012528

IEC/EN 60204

IEC/EN 60947-3

VDE 0660

CE

CSA-C22.2 No. 60947-4-1-14

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 013635 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-15126/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.