

INDUSTRIAL COMPONENT DATA

T0-4-15126/I1 218152 Y7-218152 EATON ELECTRIC Auxiliary winding switch, Contacts: 8, 20 A, front plate: 2-ST..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-15126/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-15126/I1
Catalog number	Y7-218152
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-EA676CAE07
Generated	2026-08-06

Product Overview

Auxiliary winding switch, Contacts: 8, 20 A, front plate: 2-START>0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 4 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0

T0-4-15126/I1

Auxiliary winding switch, T0, 20 A, surface mounting, 4 contact unit(s), Contacts: 8, 45 °, maintained, With 0 (Off) position, with spring-return from both directions to 0, 2-START>0

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Auxiliary winding switch, T0, 20 A, surface mounting, 4 contact unit(s), Contacts: 8, 45 °, maintained, With 0 (Off) position, with spring-return from both directions to 0, 2-START>0Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 4 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3,

Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 4 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 2-START>0

General specificationsProduct nameEaton Moeller® series T0 Auxiliary winding switchPart

no.T0-4-15126/I1EAN4015082181529Product Length/Depth137 millimetreProduct height122 millimetreProduct width80 millimetreProduct weight0.36 kilogramCompliancesVDECertificationsEN 60947

IEC 60947

EN 60204

VDE

VDE 0660

IEC/EN 60204

IEC/EN....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-15126/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.