

INDUSTRIAL COMPONENT DATA

T0-4-153/I1 222700 Y7-222700 EATON ELECTRIC Step switches, Contacts: 8, 20 A, front plate: 1-8, 45 °, mainta..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-153/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-153/I1
Catalog number	Y7-222700
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-F9C8CF26D3
Generated	2026-08-05

Product Overview

Step switches, Contacts: 8, 20 A, front plate: 1-8, 45 °, maintained, surface mounting

T0-4-153/I1

Eaton Moeller series T0 Step switch, 20 A, Surface mounting, 4 contact unit(s), Contacts: 8, Maintained, 1-8, Design: 153 Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 4 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 1-8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch

Catalog Number 222700

Model Code T0-4-153/I1

EAN 4015082227005

Product Length/Depth 137 mm

Product Height 122 mm

Product Width 80 mm

Product Weight 0.36 kg

Certifications EN 60947

IEC 60947

EN 60204

VDE

IEC/EN 60204

IEC/EN 60947

VDE 0660

IEC/EN 60947-3

Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

Features & Functions

Features Complete device in housing

Fitted with: Black thumb grip and front plate

Inscription 1-8

Number of poles Single-pole

General information

Degree of protection IP65

Degree of protection (front side) IP65

NEMA 12

Lifespan, mechanical 400,000 Operations

Mounting method Surface mounting

Mounting position As required

Number of contact units 4

Operating frequency 1200 Operations/h

Overvoltage category III

Pollution degree 3

Product category Control switches

Product category Control switches

Rated impulse withstand voltage (Uimp) 6000 V AC

Safe isolation 440 V AC, Between the contacts, According to EN 61140

Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1

Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms

Suitable for Ground mounting

Front mounting

Switching angle 45 °

Type Step switch

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temperature - max 40 °C

Ambient operating temperature (enclosed) - min -25 °C

Ambient operating temperature...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-153/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.