

INDUSTRIAL COMPONENT DATA

T0-4-15682/ST/SVB 025527 EATON ELECTRIC Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie 12A, handle red yell..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-15682/ST/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-15682/ST/SVB
Catalog number	025527
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-A8DF686FFB
Generated	2026-08-06

Product Overview

Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie=12A, handle red yellow, 0-1, 90°

General switch; Mounting stainless steel box; 6-pole + 1 NO + 1 NC; 12A; Knob Red/Yellow; 0-1; 90°

Main switch according to IEC/EN60947-3, size T0 in steel sheet enclosure, 690 V/20A, degree of protection Front IP55, with red rotary handle and yellow locking collar, lockable in O position with 3 padlocks, design general: insulating material-surface mounting enclosure, flush mounting, center mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities. All contacts are equipped with double interrupting contacts.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie=12A, handle red yellow, 0-1, 90°Main switch according to IEC/EN60947-3, size T0 in steel sheet enclosure, 690 V/20A, degree of protection Front IP55, with red rotary handle and yellow locking collar, lockable in O position with 3 padlocks, design general: insulating material-surface mounting enclosure, flush mounting, centre mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities. All contacts

are equipped with double interrupting contacts. Delivery program

Product range Main switch

maintenance switch

Repair switch Part group reference T0 Stop Function Emergency switching off function With red rotary handle and yellow

locking ring Number of poles 6 pole Auxiliary contacts 1 N/O 1 N/C Degree of Protection IP65 Design surface mounting Contact

sequence Design number 15682 Function Motor rating AC-23A, 50 - 60 Hz [P] 400 V [P] 5.5 kW Rated uninterrupted current

[I_u] 20 A Note on rated uninterrupted current I_u Rated uninterrupted current I_u is specified for max. cross-section. Number of

contact units 4 contact unit(s) Technical data

General Standards according to IEC/EN 60 204-1 Part 1

I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-15682/ST/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.