

**INDUSTRIAL COMPONENT DATA**

# T0-4-4/I1 222708 Y7-222708 EATON ELECTRIC Multi-speed switches, Contacts: 8, 20 A, One tapped winding, 2 spe..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-4/I1



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-4-4/I1       |
| Catalog number  | Y7-222708       |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-8E85C6A225   |
| Generated       | 2026-08-06      |

## Product Overview

Multi-speed switches, Contacts: 8, 20 A, One tapped winding, 2 speeds, front plate: 0-1-2, 60 °, maintained, surface mounting

T0-4-4/I1

Eaton Moeller® series T0 Multi-speed switches, T0, 20 A, surface mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 0-1-2, Design number 4

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I<sub>u</sub> = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

## Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 222708 Model Code T0-4-4/I1 EAN

4015082227081 Product Length/Depth 137 mm Product Height 122 mm Product Width 80 mm Product Weight 0.36 kg

Certifications EN 60947

EN 60204

IEC 60947

VDE

VDE 0660

IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 222708 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I<sub>u</sub> (EF001389)

20 A

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Housing material (EF001596)

Plastic

Type of control element (EF006976)

Short thumb-grip

Type of electrical connection of main circuit (EF00681...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-4/I1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.