

INDUSTRIAL COMPONENT DATA

T0-4-41/E 013842 Y7-13842 EATON ELECTRIC

Changeoverswitches, Contacts: 8, 20 A, front plate: Netz-0-Notstrom..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-41/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-41/E
Catalog number	Y7-13842
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-B8E9E383CD
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 8, 20 A, front plate: Netz-0-Notstrom, 45 °, maintained, flush mounting

Switch Switch; 8-pole; 20a; rating Plate: Netz-0-Notstrom; 45 °; flush Mount

Changeoverswitches, T0, 20 A, flush mounting, 4 contact unit(s), Contacts: 8, 45 °, maintained, With 0 (Off) position, Netz-0-Notstrom, Design number 41

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: Netz-0-Notstrom, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Changeoverswitches, T0, 20 A, flush mounting, 4 contact unit(s), Contacts: 8, 45 °, maintained, With 0 (Off) position, Netz-0-Notstrom, Design number 41Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: Netz-0-Notstrom, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN

60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton Moeller® series T0 Changeover switchPart

no.T0-4-41/EEAN4015080138426Product Length/Depth105 millimetreProduct height48 millimetreProduct width48 millimetreProduct weight0.156 kilogramCertificationsCSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

CSA-C22.2 No. 94

UL File No.: E36332

VDE 0660

UL 60947-4-1

CSA Class No.: 3211-05

UL

IEC/EN 60947

CSA File No.: 012528

CSA

IEC/EN 60204

IEC/EN 60947-3

CE

UL

CSAProduct TradenameT0Product TypeChangeover switchProduct Sub TypeNoneCatalog NotesRated Short-time

Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsEnclosure materialPlasticFitted with:Black thumb grip and front plate

0 (off) positionInscription" Netz-0-Notstrom "Number of poles4General informationDegree of protectionNEMA 1 IP65

NEMA 12Degree of protection (f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-41/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.