

INDUSTRIAL COMPONENT DATA

T0-4-41/XZ 013847 Y7-13847 EATON ELECTRIC Changeover switch, 4p, Ie 12A, supply system-0-emergency power, 45..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-41/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-41/XZ
Catalog number	Y7-13847
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-E578ECDF2D
Generated	2026-08-06

Product Overview

Changeover switch, 4p, Ie=12A, supply system-0-emergency power, 45°, maintained, replacement switch, base fixing
Switch Switch; 4-pole; 20a; rating Plate: 1-2; 45 °; Switch replacement part for case

Changeoverswitches, T0, 20 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 45 °, design no. 41

Changeover switch, Product range: Control switches, Part group reference: T0, Contacts: 8, Design: rear mounting, Basic switch, Switching angle: 45 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Changeoverswitches, T0, 20 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 45 °, design no. 41Changeover switch, Product range: Control switches, Part group reference: T0, Contacts: 8, Design: rear mounting, Basic switch, Switching angle: 45 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT0Basic functionChangeoverswitchesContacts8Designrear mounting Basic switchContact sequenceSwitching angle45 °Design number41Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]5.5 kWRated uninterrupted current [Iu]20 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units4 contact unit(s)Technical data GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40
°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock
resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V
ACElectrical characteristicsRated uninterrupted current [Iu]20 AElectrical characteristicsNote on...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-41/XZ with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.