

INDUSTRIAL COMPONENT DATA

T0-4-48/E 013870 Y7-13870 EATON ELECTRIC Multi-speed switches, Contacts: 7, 20 A, 2 speeds, 2 separate windi..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-48/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-48/E
Catalog number	Y7-13870
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-732C57386C
Generated	2026-08-04

Product Overview

Multi-speed switches, Contacts: 7, 20 A, 2 speeds, 2 separate windings, front plate: 2-0-1, 60 °, maintained, flush mounting, SOND 29

Switch Multi-speed; 7-pole; 20; 2 speeds; 2 separate windings; rating Plate: 2-0-1; 60 °; Interlock; recessed Mounting; SOND 29

Eaton Moeller® series T0 Multi-speed switches, T0, 20 A, flush mounting, 4 contact unit(s), Contacts: 7, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 29, Design number 48

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 29, Contacts: 7, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 013870 Model Code T0-4-48/E EAN 4015080138709 Product Length/Depth 105 mm Product Height 48 mm Product Width 48 mm Product Weight 0.156 kg
Certifications CSA
UL

UL File No.: E36332

VDE 0660

CE

CSA Class No.: 3211-05

IEC/EN 60204

IEC/EN 60947

UL 60947-4-1

CSA-C22.2 No. 94

UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

CSA File No.: 012528

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 013870 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-48/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.