

## INDUSTRIAL COMPONENT DATA

**T0-4-8419/Z 014034 Y7-14034 EATON ELECTRIC Star-delta switches, Contacts: 7, 20 A, front plate: 0-Y-D, 90 °, ..**

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-8419/Z



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-4-8419/Z     |
| Catalog number  | Y7-14034        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-23EA1BB7AE   |
| Generated       | 2026-08-06      |

**Product Overview**

Star-delta switches, Contacts: 7, 20 A, front plate: 0-Y-D, 90 °, maintained, rear mounting, SOND 27  
Switch Star-delta; 7-pole; 20a; rating Plate: 0 -, And-D; 90 °; Interlocking; Installation bottom panel; SOND 27  
Eaton Moeller® series T0 Star-delta switches, T0, 20 A, rear mounting, 4 contact unit(s), Contacts: 7, 90 °, maintained, With 0 (Off) position, 0-Y-D, SOND 27, Design number 8419  
Star-delta switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 27, Contacts: 7, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I<sub>u</sub> = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Disconnectors and Cam Switches

**Additional Product Information**

## General specifications

Product Name Eaton Moeller® series T0 Star-delta switch Catalog Number 014034 Model Code T0-4-8419/Z EAN 4015080140344 Product Length/Depth 147 mm Product Height 48 mm Product Width 48 mm Product Weight 0.187 kg

Certifications UL 60947-4-1

UL

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

CSA

UL File No.: E36332

CSA File No.: 012528

VDE 0660

IEC/EN 60204

CE

CSA-C22.2 No. 94

CSA Class No.: 3211-05

IEC/EN 60947-3

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (I<sub>cs</sub>) for a time of 1 second

ETIM for 014034 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I<sub>u</sub> (EF001389)

20 A

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing m...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / T0-4-8419/Z with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.