

INDUSTRIAL COMPONENT DATA

T0-5-124/E 014088 Y7-14088 EATON ELECTRIC Multi-speed switches, Contacts: 9, 20 A, One tapped winding, 2 spe..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-124/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-124/E
Catalog number	Y7-14088
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-C1CE9BFCCD
Generated	2026-08-06

Product Overview

Multi-speed switches, Contacts: 9, 20 A, One tapped winding, 2 speeds, front plate: 2-0-1, 60 °, maintained, flush mounting, SOND 30

Switch Multi-speed; 9-pole; 20a; 1 winding threading; 2 speeds; rating Plate: 2-0-1; 60 °; Interlock; recessed Mounting; SOND 30

Eaton Moeller® series T0 Multi-speed switches, T0, 20 A, flush mounting, 5 contact unit(s), Contacts: 9, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 30, Design number 124

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 30, Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 014088 Model Code T0-5-124/E EAN 4015080140887 Product Length/Depth 114 mm Product Height 48 mm Product Width 48 mm Product Weight 0.147 kg
Certifications UL Category Control No.: NLRV
CSA Class No.: 3211-05

CSA File No.: 012528

UL

IEC/EN 60947

CSA

CSA-C22.2 No. 94

IEC/EN 60947-3

IEC/EN 60204

UL 60947-4-1

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

CE

VDE 0660 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 014088 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing mater...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-124/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.