

INDUSTRIAL COMPONENT DATA

T0-5-15012/Z 014104 Y7-14104 EATON ELECTRIC Step switches, Contacts: 10, 20 A, front plate: 1-5, 45 °, Unint..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-15012/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-15012/Z
Catalog number	Y7-14104
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-27F3F40FF7
Generated	2026-08-05

Product Overview

Step switches, Contacts: 10, 20 A, front plate: 1-5, 45 °, Uninterruptible, maintained, rear mounting

Switch steps; 10-pole; 20a; rating Plate: 1-5; 45 °; Power; Latching; Mounting bottom panel

Eaton Moeller® series T0 Step switches, T0, 20 A, rear mounting, 5 contact unit(s), Contacts: 10, 45 °, maintained, Without 0 (Off) position, 1-5, Design number 15012

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate,

Contacts: 10, Contact behavior: Uninterruptible, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 5 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 1-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 014104 Model Code T0-5-15012/Z EAN

4015080141044 Product Length/Depth 156 mm Product Height 48 mm Product Width 48 mm Product Weight 0.211 kg

Certifications CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

UL File No.: E36332

CSA Class No.: 3211-05

UL

CE

IEC/EN 60947

CSA-C22.2 No. 94

IEC/EN 60204

UL 60947-4-1

VDE 0660

CSA

CSA File No.: 012528

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 014104 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-15012/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.