

## INDUSTRIAL COMPONENT DATA

**T0-5-15150/E 014145 Y7-14145 EATON ELECTRIC Step switches, Contacts: 9, 20 A, front plate: 1-3, 45 °, mainta..**

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-15150/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-5-15150/E    |
| Catalog number  | Y7-14145        |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-292A9BB377   |
| Generated       | 2026-08-04      |

**Product Overview**

Step switches, Contacts: 9, 20 A, front plate: 1-3, 45 °, maintained, flush mounting

Switch steps; 9-pole; 20a; rating Plate: 1-3; 45 °; Interlock; recessed Mounting

Eaton Moeller® series T0 Step switches, T0, 20 A, flush mounting, 5 contact unit(s), Contacts: 9, 45 °, maintained, Without 0 (Off) position, 1-3, Design number 15150

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate,

Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance:

maintained, Without 0 (Off) position, 5 contact unit(s), Rated uninterrupted current: I<sub>u</sub>= 20 A, front plate: 1-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

**Additional Product Information**

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 014145 Model Code T0-5-15150/E EAN

4015080141457 Product Length/Depth 114 mm Product Height 48 mm Product Width 48 mm Product Weight 0.147 kg

Certifications UL

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

IEC/EN 60947

UL Category Control No.: NLRV  
CSA Class No.: 3211-05  
CSA-C22.2 No. 94  
CE  
CSA File No.: 012528  
IEC/EN 60204  
CSA  
UL File No.: E36332  
VDE 0660 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second  
ETIM for 014145 Low-voltage industrial controls and switchgear (EC002611)  
Feature Name  
Feature Value  
Type of switch (EF003496)  
Level switch  
Number of poles (EF001391)  
3  
Max. rated operation voltage U<sub>e</sub> AC (EF007355)  
690 V  
Rated permanent current I<sub>u</sub> (EF001389)  
20 A  
Number of switch positions (EF000231)  
3  
With zero (off) position (EF001416)  
No  
With retraction in 0-position (EF002428)  
No  
Device construction (EF008240)  
Built-in device  
Width in number of modular spacings (EF002950)  
0  
Suitable for floor mounting (EF007243)  
No  
Suitable for front mounting (EF007246)  
Yes  
Suitable for distribution board installation (EF007262)  
No  
Suitable for intermediate mounting (EF007264)  
No  
Complete device in housing (EF007317)  
No  
Type of control element (EF006976)  
Toggle  
Front shield size (EF007176)  
48x48 mm  
Degree of protection (IP), front side (EF003118)  
IP65  
Degree of protection (NEMA), front side (EF011961)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-15150/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.