

INDUSTRIAL COMPONENT DATA

T0-5-15203/E 014160 Y7-14160 EATON ELECTRIC Multi-speed switches, Contacts: 9, 20 A, One tapped winding, 2 s..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-15203/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-15203/E
Catalog number	Y7-14160
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-5F16D0B578
Generated	2026-08-06

Product Overview

Multi-speed switches, Contacts: 9, 20 A, One tapped winding, 2 speeds, front plate: 1-2, 90 °, maintained, flush mounting
Switch Multi-speed; 9-pole; 20a; 1 winding threading; 2 speeds; rating Plate: 1-2; 90 °; Latch; flush Mount
Multi-speed switches, T0, 20 A, flush mounting, 5 contact unit(s), Contacts: 9, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 15203
Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 014160 Model Code T0-5-15203/E EAN 4015080141600 Product Length/Depth 114 mm Product Height 48 mm Product Width 48 mm Product Weight 0.147 kg
Certifications UL Category Control No.: NLRV
IEC/EN 60204
VDE 0660
CSA-C22.2 No. 94

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

CSA

CSA File No.: 012528

IEC/EN 60947

CSA Class No.: 3211-05

CE

UL

IEC/EN 60947-3

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 014160 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-15203/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.