

## INDUSTRIAL COMPONENT DATA

**T0-5-15892/E 014310 Y7-14310 EATON ELECTRIC Star-delta switches, Contacts: 10, 20 A, front plate: B 0-Y-D, 6..**

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-15892/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-5-15892/E    |
| Catalog number  | Y7-14310        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-ED7407D074   |
| Generated       | 2026-08-06      |

**Product Overview**

Star-delta switches, Contacts: 10, 20 A, front plate: B>0-Y-D, 60 °, maintained, flush mounting  
Switch Star-Triangle; 10-pole; 20a; rating Plate: B>0-And-D; 60 °; Interlock; recessed Mounting  
Eaton Moeller® series T0 Star-delta switches, T0, 20 A, flush mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained, With 0 (Off) position, With spring-return to 0, B>0-Y-D, Design number 15892  
Star-delta switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, With spring-return to 0, front plate: B>0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                  |
|--------------|--------------------------------------------------|
| Catalog path | EATON - MOELLER > Disconnectors and Cam Switches |
|--------------|--------------------------------------------------|

**Additional Product Information**

## General specifications

Product Name Eaton Moeller® series T0 Star-delta switch Catalog Number 014310 Model Code T0-5-15892/E EAN 4015080143109 Product Length/Depth 114 mm Product Height 48 mm Product Width 48 mm Product Weight 0.147 kg

Certifications UL File No.: E36332

UL Category Control No.: NLRV

CSA Class No.: 3211-05

IEC/EN 60204

UL

CSA File No.: 012528

IEC/EN 60947

CSA

CE

IEC/EN 60947-3

CSA-C22.2 No. 94

VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (I<sub>cs</sub>) for a time of 1 second

ETIM for 014310 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Rated permanent current I<sub>u</sub> (EF001389)

20 A

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-15892/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.