

INDUSTRIAL COMPONENT DATA

T0-5-15896/E 014466 Y7-14466 EATON ELECTRIC Reversing star-delta switches, Contacts: 10, 20 A, front plate: ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-15896/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-15896/E
Catalog number	Y7-14466
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-446F58ADC3
Generated	2026-08-05

Product Overview

Reversing star-delta switches, Contacts: 10, 20 A, front plate: D-Y-0-Y-D, 60 °, maintained, flush mounting
Switch Star-delta with reversing; 10-pole; 20a; rating Plate: D-y-0-y-D; 60 °; Interlock; recessed Mounting
Eaton Moeller® series T0 Reversing star-delta switches, T0, 20 A, flush mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained, With 0 (Off) position, D-Y-0-Y-D, Design number 15896
Turnaround star-delta switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: D-Y-0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Turnaround star-delta switch Catalog Number 014466 Model Code T0-5-15896/E
EAN 4015080144663 Product Length/Depth 114 mm Product Height 48 mm Product Width 48 mm Product Weight 0.147 kg

Certifications IEC/EN 60947

IEC/EN 60204

UL Category Control No.: NLRV

UL File No.: E36332

CSA-C22.2 No. 94

UL

CSA

CSA File No.: 012528

IEC/EN 60947-3

VDE 0660

CSA-C22.2 No. 60947-4-1-14

CE

CSA Class No.: 3211-05

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 014466 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Turnaround star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-15896/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.