

INDUSTRIAL COMPONENT DATA

T0-5-15899/EZ 014542 Y7-14542 EATON ELECTRIC Star-delta switches, Contacts: 10, 20 A, front plate: 0-Y-D, 60..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-15899/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-15899/EZ
Catalog number	Y7-14542
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-271C9AB46B
Generated	2026-08-06

Product Overview

Star-delta switches, Contacts: 10, 20 A, front plate: 0-Y-D, 60 °, maintained, centre mounting, SOND 28
Switch Star-Triangle; 10-pole; 20a; rating Plate: 0 -, And-D; 60 °; Interlock; recessed Mounting with central fixing; SOND 28
Eaton Moeller® series T0 Star-delta switches, T0, 20 A, center mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained,
With 0 (Off) position, 0-Y-D, SOND 28, Design number 15899
Star-delta switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes:
SOND 28, Contacts: 10, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 60 °, Switching
performance: maintained, With 0 (Off) position, front plate: 0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW,
Rated uninterrupted current: Iu = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,
Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Star-delta switch Catalog Number 014542 Model Code T0-5-15899/EZ EAN
4015080145424 Product Length/Depth 134 mm Product Height 48 mm Product Width 48 mm Product Weight 0.201 kg

Certifications CSA File No.: 012528

CSA Class No.: 3211-05

UL

UL 60947-4-1

CSA

IEC/EN 60947-3

UL Category Control No.: NLRV

UL File No.: E36332

IEC/EN 60204

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

VDE 0660

CE

CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 014542 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-15899/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.