

INDUSTRIAL COMPONENT DATA

T0-6-15083/E 015343 Y7-15343 EATON ELECTRIC Star-delta switches, Contacts: 11, 20 A, front plate: 0-Y-1-D, 6..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-15083/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-15083/E
Catalog number	Y7-15343
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-17C5414AD9
Generated	2026-08-06

Product Overview

Star-delta switches, Contacts: 11, 20 A, front plate: 0-Y-1-D, 60 °, maintained, flush mounting
Switch Star-Triangle; 11-pole; 20a; rating Plate: 0-And-1-D; 60 °; Interlock; recessed Mounting
Eaton Moeller® series T0 Star-delta switches, T0, 20 A, flush mounting, 6 contact unit(s), Contacts: 11, 60 °, maintained, With 0 (Off) position, 0-Y-1-D, Design number 15083
Star-delta switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 11, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-1-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Star-delta switch Catalog Number 015343 Model Code T0-6-15083/E EAN 4015080153436 Product Length/Depth 124 mm Product Height 48 mm Product Width 48 mm Product Weight 0.16 kg

Certifications CSA File No.: 012528

IEC/EN 60947-3

CSA

UL 60947-4-1

VDE 0660

CE

UL

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332

UL Category Control No.: NLRV

IEC/EN 60947

CSA Class No.: 3211-05

CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 015343 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-15083/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.