

## INDUSTRIAL COMPONENT DATA

**T0-6-15249/IVS 015416 Y7-15416 EATON ELECTRIC Step switches, Contacts: 11, 20 A, front plate: 0-11, 30 °, ma..**

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-15249/IVS



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-6-15249/IVS  |
| Catalog number  | Y7-15416        |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-9AC1FEB8FE   |
| Generated       | 2026-08-05      |

**Product Overview**

Step switches, Contacts: 11, 20 A, front plate: 0-11, 30 °, maintained, service distribution board mounting

Switch steps; 11-pole; 20a; rating Plate: 0-11; 30 °; Interlock; Mounting in control cabinet

Eaton Moeller® series T0 Step switches, T0, 20 A, service distribution board mounting, 6 contact unit(s), Contacts: 11, 30 °, maintained, With 0 (Off) position, 0-11, Design number 15249

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 11, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 30 °, Switching performance: maintained, With 0 (Off) position, 6 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 0-11

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

**Additional Product Information**

## General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 015416 Model Code T0-6-15249/IVS EAN

4015080154167 Product Length/Depth 130 mm Product Height 55 mm Product Width 54 mm Product Weight 0.229 kg

Certifications UL 60947-4-1

CSA-C22.2 No. 94

UL

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

CSA

IEC/EN 60204

UL File No.: E36332

CE

IEC/EN 60947-3

CSA File No.: 012528

IEC/EN 60947

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 015416 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

1

Max. rated operation voltage U<sub>e</sub> AC (EF007355)

690 V

Rated permanent current I<sub>u</sub> (EF001389)

20 A

Number of switch positions (EF000231)

12

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

4

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-15249/IVS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.