

INDUSTRIAL COMPONENT DATA

T0-6-154/EZ 015430 Y7-15430 EATON ELECTRIC Multi-speed switches, Contacts: 12, 20 A, 3 speeds, 2 separate wi..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-154/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-154/EZ
Catalog number	Y7-15430
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F0130B48E2
Generated	2026-08-06

Product Overview

Multi-speed switches, Contacts: 12, 20 A, 3 speeds, 2 separate windings, front plate: 0-1-2-3, 60 °, maintained, centre mounting

Switch Multi-speed; 12-pole; 20; 2 speeds; 2 separate windings; rating Plate: 0-1-2-3; 60 °; Interlock; recessed Mounting with central fixing

Eaton Moeller® series T0 Multi-speed switches, T0, 20 A, centre mounting, 6 contact unit(s), Contacts: 12, 60 °, maintained, With 0 (Off) position, 0-1-2-3, Design number 154

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 12, Degree of Protection: Front IP65, Design: center mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2-3, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 015430 Model Code T0-6-154/EZ EAN 4015080154303 Product Length/Depth 144 mm Product Height 48 mm Product Width 48 mm Product Weight 0.24 kg
Certifications CSA-C22.2 No. 94
IEC/EN 60947

UL

CSA-C22.2 No. 60947-4-1-14

CSA File No.: 012528

UL File No.: E36332

CSA Class No.: 3211-05

IEC/EN 60204

CSA

IEC/EN 60947-3

UL 60947-4-1

VDE 0660

CE

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 015430 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

true

With retraction in 0-position (EF002428)

false

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

false

Suitable for front mounting (EF007246)

true

Suitable for distribution board installation (EF007262)

false

Suitable for intermediate mounting (EF007264)

false

Complete device in housing (EF007317)

false

H...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-154/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.