

INDUSTRIAL COMPONENT DATA

T0-6-15893/Z 015453 Y7-15453 EATON ELECTRIC Star-delta switches, Contacts: 11, 20 A, front plate: B 0-Y-D, 6..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-15893/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-15893/Z
Catalog number	Y7-15453
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-3476CDDCC1
Generated	2026-08-06

Product Overview

Star-delta switches, Contacts: 11, 20 A, front plate: B>0-Y-D, 60 °, maintained, rear mounting, SOND 29
Switch Star-Triangle; 11-pole; 20a; rating Plate: B>0-And-D; 60 °; Interlocking; Installation bottom panel; SOND 29
Eaton Moeller® series T0 Star-delta switches, T0, 20 A, rear mounting, 6 contact unit(s), Contacts: 11, 60 °, maintained,
With 0 (Off) position, With spring-return to 0, B>0-Y-D, SOND 29, Design number 15893
Star-delta switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes:
SOND 29, Contacts: 11, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching
performance: maintained, With 0 (Off) position, With spring-return to 0, front plate: B>0-Y-D, Motor rating AC-23A, 50 - 60
Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660,
IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Star-delta switch Catalog Number 015453 Model Code T0-6-15893/Z EAN
4015080154532 Product Length/Depth 166 mm Product Height 48 mm Product Width 48 mm Product Weight 0.235 kg

Certifications VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL Category Control No.: NLRV

CSA File No.: 012528

CSA-C22.2 No. 94

IEC/EN 60947-3

UL File No.: E36332

IEC/EN 60204

IEC/EN 60947

CSA Class No.: 3211-05

UL

CE

CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 015453 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-15893/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.