

INDUSTRIAL COMPONENT DATA

T0-7-8076/E 015969 Y7-15969 EATON ELECTRIC Measuring point changeover switch, Contacts: 14, 20 A, front plat..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-7-8076/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-7-8076/E
Catalog number	Y7-15969
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-73056D7315
Generated	2026-08-03

Product Overview

Measuring point changeover switch, Contacts: 14, 20 A, front plate: 6-TEST-OFF-1-2-3-4-5, 45 °, maintained, flush mounting

Switch point of measurement; 14-pole; 20a; rating Plate: 6-TEST-OFF-1-2-3-4-5; 45 °; Interlock; recessed Mounting Eaton Moeller® series T0 Measuring point changeover switch, T0, 20 A, flush mounting, 7 contact unit(s), Contacts: 14, 45 °, maintained, With 0 (Off) position, 6-TEST-OFF-1-2-3-4-5, Design number 8076

Measuring point changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 14, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 6-TEST-OFF-1-2-3-4-5, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Measuring point changeover switch Catalog Number 015969 Model Code T0-7-8076/E EAN 4015080159698 Product Length/Depth 133 mm Product Height 48 mm Product Width 48 mm Product Weight 0.184 kg Certifications CSA File No.: 012528 IEC/EN 60947 CSA Class No.: 3211-05

CSA-C22.2 No. 94

IEC/EN 60204

CSA

UL Category Control No.: NLRV

UL File No.: E36332

CE

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

VDE 0660

UL

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 015969 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

On/Off switch

Number of poles (EF001391)

6

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

H...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-7-8076/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.