

INDUSTRIAL COMPONENT DATA

T0-8-15146/E 016089 Y7-16089 EATON ELECTRIC Step switches, Contacts: 15, 20 A, front plate: 0-5, 45 °, maint..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-8-15146/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-8-15146/E
Catalog number	Y7-16089
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-14BFA0A042
Generated	2026-08-06

Product Overview

Step switches, Contacts: 15, 20 A, front plate: 0-5, 45 °, maintained, flush mounting
Switch steps; 15-pole; 20a; rating Plate: 0-5; 45 °; Interlock; recessed Mounting
Eaton Moeller® series T0 Step switches, T0, 20 A, flush mounting, 8 contact unit(s), Contacts: 15, 45 °, maintained, With 0 (Off) position, 0-5, Design number 15146
Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,
Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate,
Contacts: 15, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance:
maintained, With 0 (Off) position, 8 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 0-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 016089 Model Code T0-8-15146/E EAN 4015080160892 Product Length/Depth 143 mm Product Height 48 mm Product Width 48 mm Product Weight 0.208 kg
Certifications CSA
UL File No.: E36332
UL Category Control No.: NLRV
VDE 0660
CSA-C22.2 No. 60947-4-1-14

UL
CE
IEC/EN 60947
IEC/EN 60947-3
IEC/EN 60204
CSA File No.: 012528
UL 60947-4-1
CSA Class No.: 3211-05
CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 016089 Low-voltage industrial controls and switchgear (EC002611)
Feature Name
Feature Value
Type of switch (EF003496)
Level switch
Number of poles (EF001391)
3
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated permanent current Iu (EF001389)
20 A
Number of switch positions (EF000231)
6
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Device construction (EF008240)
Built-in device
Width in number of modular spacings (EF002950)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
No
Type of control element (EF006976)
Toggle
Front shield size (EF007176)
48x48 mm
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-8-15146/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.