

INDUSTRIAL COMPONENT DATA

T0-9-15103/Z 016221 Y7-16221 EATON ELECTRIC Multi-speed switches, Contacts: 17, 20 A, 3 speeds, front plate:..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-9-15103/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-9-15103/Z
Catalog number	Y7-16221
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-796D8F19F5
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 17, 20 A, 3 speeds, front plate: 1-2-3, 60 °, maintained, rear mounting, SOND 28
Switch Multi-speed; 17-pole; 20a; 3 speeds; rating Plate: 1-2-3; 60 °; Interlocking; Installation bottom panel; SOND 28
Eaton Moeller® series T0 Multi-speed switches, T0, 20 A, rear mounting, 9 contact unit(s), Contacts: 17, 60 °, maintained, Without 0 (Off) position, 1-2-3, SOND 28, Design number 15103

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 28, Contacts: 17, Degree of Protection: Front IP65, Design: rear mounting, switching function: 3 speeds, Switching angle: 60 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2-3, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 9 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 016221 Model Code T0-9-15103/Z EAN 4015080162216 Product Length/Depth 94 mm Product Height 48 mm Product Width 48 mm Product Weight 0.307 kg

Certifications CSA File No.: 012528

CSA-C22.2 No. 94

IEC/EN 60204

IEC/EN 60947

UL 60947-4-1
CSA Class No.: 3211-05
CSA-C22.2 No. 60947-4-1-14
IEC/EN 60947-3
UL File No.: E36332
CE
CSA
UL Category Control No.: NLRV
VDE 0660
UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 016221 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Pole switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current Iu (EF001389)
20 A
Rated operation current Ie at AC-3, 400 V (EF001392)
11.5 A
Rated operation power at AC-3, 400 V (EF001364)
4 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
Yes
Complete device in housing (EF007317)
No

Housing material...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-9-15103/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.