

INDUSTRIAL COMPONENT DATA

T3-1-15059/E 016374 Y7-16374 EATON ELECTRIC Operation mode switch, Contacts: 2, 32 A, front plate: Aus-Betri..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-1-15059/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-1-15059/E
Catalog number	Y7-16374
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-B9CB606B73
Generated	2026-08-04

Product Overview

Operation mode switch, Contacts: 2, 32 A, front plate: Aus-Betrieb-Prüfen, 45 °, maintained, flush mounting
Operation mode switch; 2-pole; 32; rating Plate: Aus-Betrieb-Prüfen; 45 °; Interlock; recessed Mounting
Eaton Moeller® series T3 Operation mode switch, T3, 32 A, flush mounting, 1 contact unit(s), Contacts: 2, 45 °, maintained, Without 0 (Off) position, Aus-Betrieb-Prüfen, Design number 15059
Operation mode switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 2, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 1 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: Aus-Betrieb-Prüfen

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Operation mode switch Catalog Number 016374 Model Code T3-1-15059/E EAN 4015080163749 Product Length/Depth 79 mm Product Height 54 mm Product Width 61 mm Product Weight 0.11 kg

Certifications IEC/EN 60947

VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL

CE

UL Category Control No.: NLRV

IEC/EN 60204

UL File No.: E36332

IEC/EN 60947-3

CSA-C22.2 No. 94

CSA

CSA File No.: 012528

CSA Class No.: 3211-05

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 016374 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

32 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-1-15059/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.