

INDUSTRIAL COMPONENT DATA

T3-11-8258/XZ 003887 Y7-3887 EATON ELECTRIC Step switch, 2p, Ie 25A, 1-11, 30°, maintained, replacement swit..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-11-8258/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-11-8258/XZ
Catalog number	Y7-3887
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-100C6280A7
Generated	2026-08-04

Product Overview

Step switch, 2p, Ie=25A, 1-11, 30°, maintained, replacement switch, base fixing

Step switch 2 poles 32 A Indicator plate: 1...11 30°

T3, 32 A, rear mounting, Basic switch, 11 contact unit(s), Contacts: 22, design no. 8258

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 22, Design: rear mounting, Basic switch, 11 contact unit(s), Rated uninterrupted current: Iu= 32 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

T3, 32 A, rear mounting, Basic switch, 11 contact unit(s), Contacts: 22, design no. 8258Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 22, Design: rear mounting, Basic switch, 11 contact unit(s), Rated uninterrupted current: Iu= 32 ADelivery program

Product rangeControl switchesPart group referenceT3Contacts22Designrear mounting

Basic switchContact sequenceDesign number8258Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [Iu]32 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units11 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40 °C
Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V AC
Electrical characteristics Rated uninterrupted current [Iu] 32 A Electrical characteristics Note on rated uninterrupted current !u Rated uninterrupted current Iuis specified for max. cross-section. Load rating with intermittent operation, class 12AB....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-11-8258/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.