

INDUSTRIAL COMPONENT DATA

T3-2-15042/E 047599 Y7-47599 EATON ELECTRIC ON-OFF switches, Contacts: 4, 32 A, front plate: 0-1-0-1, 90 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-15042/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-15042/E
Catalog number	Y7-47599
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-C4F1FE01CD
Generated	2026-08-06

Product Overview

ON-OFF switches, Contacts: 4, 32 A, front plate: 0-1-0-1, 90 °, maintained, flush mounting
Disconnect switch ON-OFF; 4 poles; 32; rating Plate: 0-1-0-1; 90 °; Latch; flush Mount
Eaton Moeller® series T3 ON-OFF switches, T3, 32 A, flush mounting, 2 contact unit(s), Contacts: 4, 90 °, maintained, With 0 (Off) position, 0-1-0-1, Design number 15042
On-Off switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,
Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate,
Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance:
maintained, With 0 (Off) position, 2 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: 0-1-0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 On-off switch Catalog Number 047599 Model Code T3-2-15042/E EAN
4015080475996 Product Length/Depth 91 mm Product Height 54 mm Product Width 61 mm Product Weight 0.172 kg
Certifications CSA-C22.2 No. 60947-4-1-14
VDE 0660
CSA
IEC/EN 60947
IEC/EN 60947-3

UL Category Control No.: NLRV

UL

CSA Class No.: 3211-05

CSA-C22.2 No. 94

IEC/EN 60204

CSA File No.: 012528

CE

UL File No.: E36332

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 047599 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

4

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

32 A

Number of switch positions (EF000231)

4

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-15042/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.