

INDUSTRIAL COMPONENT DATA

T3-2-15125/Z 017810 Y7-17810 EATON ELECTRIC Auxiliary winding switch, Contacts: 4, 32 A, front plate: 0 Au..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-15125/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-15125/Z
Catalog number	Y7-17810
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-CECC31C426
Generated	2026-08-05

Product Overview

Auxiliary winding switch, Contacts: 4, 32 A, front plate: 0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to 0, 2 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: 0

Switch auxiliary winding; 4 poles; 32; rating Plate: 0

Eaton Moeller® series T3 Auxiliary winding switch, T3, 32 A, rear mounting, 2 contact unit(s), Contacts: 4, 45 °, momentary/maintained, With 0 (Off) position, With spring-return to 0, 0

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Auxiliary winding switch Catalog Number 017810 Model Code T3-2-15125/Z EAN 4015080178101 Product Length/Depth 133 mm Product Height 54 mm Product Width 61 mm Product Weight 0.195 kg

Certifications CSA Class No.: 3211-05

CSA File No.: 012528

UL 60947-4-1

UL File No.: E36332

VDE 0660

CSA

CSA-C22.2 No. 94

IEC/EN 60947-3

CE

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

IEC/EN 60947

UL

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 017810 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

32 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-15125/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.