

INDUSTRIAL COMPONENT DATA

**T3-2-2092CH/I2/SVB-SI-CHD-230V 172956 Y7-172956 EATON
ELECTRIC SUVA safety switches, 32 A, Emergency-Stop fu..**

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-2092CH/I2/SVB-SI-CHD-230V



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-2092CH/I2/SVB-SI-CHD-230V
Catalog number	Y7-172956
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C53F6E952E
Generated	2026-08-06

Product Overview

SUVA safety switches, 32 A, Emergency-Stop function, Lockable in position 0 with cover interlock, surface mounting, with warning label „safety switch”

T3-2-2092CH/I2/SVB-SI-CHD-230V

Eaton Moeller® series T3 SUVA safety switches, T3, 32 A, surface mounting, 2 N/O, 2 N/C, Emergency switching off function, with warning label „safety switch”, Indicator light 230 V

SUVA safety switch, Product range: SUVA safety switches, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, Notes: with warning label „safety switch”, Information about equipment supplied: Indicator light 230 V, Locking facility: Lockable in position 0 with cover interlock, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 SUVA safety switch Catalog Number 172956 Model Code

T3-2-2092CH/I2/SVB-SI-CHD-230V EAN 4015081695447 Product Length/Depth 185 mm Product Height 124 mm Product Width 108 mm Product Weight 0.5 kg Certifications IEC/EN 60204

IEC/EN 60947

VDE 0660

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 172956 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

Yes

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

32 A

Rated permanent current at AC-23, 400 V (EF011777)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

11 kW

Rated short-time withstand current I_{cw} (EF007050)

0.65 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current I_q (EF001444)

1 kA

Number of poles (EF001391)

2

Number of auxiliary contacts as normally closed contact (EF001377)

2

Number of auxiliary contacts as normally open contact (EF001376)

2

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-2092CH/I2/SVB-SI-CHD-230V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.