

INDUSTRIAL COMPONENT DATA

T3-2-39/Z 018284 Y7-18284 EATON ELECTRIC Multi-speed switches, Contacts: 4, 32 A, 2 speeds, 2 separate windi..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-39/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-39/Z
Catalog number	Y7-18284
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-3C68891318
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 4, 32 A, 2 speeds, 2 separate windings, front plate: 1-2, 90 °, maintained, rear mounting, SOND 30

Switch Multi-speed; 4-pole; 32; 2 speeds; 2 separate windings; rating Plate: 1-2; 90 °; Interlocking; Installation bottom panel; SOND 30

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, rear mounting, 2 contact unit(s), Contacts: 4, 90 °, maintained, Without 0 (Off) position, 1-2, SOND 30, Design number 39

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 30, Contacts: 4, Degree of Protection: Front IP65, Design: rear mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 018284 Model Code T3-2-39/Z EAN 4015080182849 Product Length/Depth 133 mm Product Height 54 mm Product Width 61 mm Product Weight 0.195 kg
Certifications UL Category Control No.: NLRV
VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL

CSA Class No.: 3211-05

IEC/EN 60947-3

CSA File No.: 012528

IEC/EN 60947

CE

UL File No.: E36332

IEC/EN 60204

CSA-C22.2 No. 94

UL 60947-4-1

CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 018284 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

2

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing material (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-39/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.