

INDUSTRIAL COMPONENT DATA

T3-2-96/EZ 018586 Y7-18586 EATON ELECTRIC step switch for heating, Contacts: 3, 32 A, front plate: 0-3, 60 °..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-96/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-96/EZ
Catalog number	Y7-18586
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-897D922DE4
Generated	2026-08-05

Product Overview

step switch for heating, Contacts: 3, 32 A, front plate: 0-3, 60 °, maintained, centre mounting
Switch steps for heating; 3-pole; 32; rating Plate: 0-3; 60 °; Interlock; recessed Mounting with central fixing
Eaton Moeller® series T3 step switch for heating, T3, 32 A, centre mounting, 2 contact unit(s), Contacts: 3, 60 °, maintained, With 0 (Off) position, 0-3, Design number 96
Step switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-3, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 018586 Model Code T3-2-96/EZ EAN 4015080185864 Product Length/Depth 113 mm Product Height 54 mm Product Width 61 mm Product Weight 0.179 kg

Certifications CSA

CSA File No.: 012528

CSA-C22.2 No. 94

UL File No.: E36332

UL Category Control No.: NLRV

UL 60947-4-1

VDE 0660

CSA Class No.: 3211-05

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

CE

IEC/EN 60947-3

IEC/EN 60947

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 018586 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

1

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF001596)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-96/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.