

INDUSTRIAL COMPONENT DATA

T3-3-15026/EZ 018682 Y7-18682 EATON ELECTRIC Step switches, Contacts: 5, 32 A, front plate: 0-5, 45 °, Unint..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-15026/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-15026/EZ
Catalog number	Y7-18682
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-F95E771A10
Generated	2026-08-04

Product Overview

Step switches, Contacts: 5, 32 A, front plate: 0-5, 45 °, Uninterruptible, maintained, centre mounting

Switch steps; 5 poles; 32; Plate indicator: 0-5; 45 °; Uninterruptible power supply; Interlock; recessed Mounting with central fixing

Eaton Moeller® series T3 Step switches, T3, 32 A, centre mounting, 3 contact unit(s), Contacts: 5, 45 °, maintained, With 0 (Off) position, 0-5, Design number 15026

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 5, Contact behavior: Uninterruptible, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 3 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: 0-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 018682 Model Code T3-3-15026/EZ EAN 4015080186823 Product Length/Depth 124 mm Product Height 54 mm Product Width 61 mm Product Weight 0.233 kg

Certifications IEC/EN 60947

UL File No.: E36332

CSA

CSA File No.: 012528

CSA Class No.: 3211-05

IEC/EN 60204

UL 60947-4-1

UL

UL Category Control No.: NLRV

CE

VDE 0660

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 018682 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

32 A

Number of switch positions (EF000231)

6

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-15026/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.