

INDUSTRIAL COMPONENT DATA

T3-3-15190/E 018796 Y7-18796 EATON ELECTRIC Reversing switches, Contacts: 6, 32 A, front plate: 2-0-1, 90 °,..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-15190/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-15190/E
Catalog number	Y7-18796
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-B71E700B5E
Generated	2026-08-06

Product Overview

Reversing switches, Contacts: 6, 32 A, front plate: 2-0-1, 90 °, maintained, flush mounting

Reversing switch; 6-pole; 32; rating Plate: 2-0-1; 90 °; Latch; flush Mount

Eaton Moeller® series T3 Reversing switches, T3, 32 A, flush mounting, 3 contact unit(s), Contacts: 6, 90 °, maintained, With 0 (Off) position, 2-0-1, Design number 15190

Reversing switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Reversing switch Catalog Number 018796 Model Code T3-3-15190/E EAN 4015080187967 Product Length/Depth 102 mm Product Height 54 mm Product Width 61 mm Product Weight 0.21 kg

Certifications UL

UL Category Control No.: NLRV

CE

CSA File No.: 012528

CSA-C22.2 No. 94

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

IEC/EN 60947

UL File No.: E36332

CSA

IEC/EN 60204

VDE 0660

CSA Class No.: 3211-05 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 018796 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing mater...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-15190/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.