

INDUSTRIAL COMPONENT DATA

T3-3-2/EZ 018947 Y7-18947 EATON ELECTRIC Reversing switches, Contacts: 5, 32 A, front plate: 2-0-1, 45 °, ma..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-2/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-2/EZ
Catalog number	Y7-18947
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-7DCBAA995C
Generated	2026-08-05

Product Overview

Reversing switches, Contacts: 5, 32 A, front plate: 2-0-1, 45 °, maintained, centre mounting
Reversing switch; 5-pole; 32; rating Plate: 2-0-1; 45 °; Interlock; recessed Mounting with central fixing
Eaton Moeller® series T3 Reversing switches, T3, 32 A, center mounting, 3 contact unit(s), Contacts: 5, 45 °, maintained, With 0 (Off) position, 2-0-1, Design number 2
Reversing switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 5, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Reversing switch Catalog Number 018947 Model Code T3-3-2/EZ EAN 4015080189473 Product Length/Depth 124 mm Product Height 54 mm Product Width 61 mm Product Weight 0.233 kg

Certifications CSA Class No.: 3211-05

IEC/EN 60947-3

CSA

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

IEC/EN 60947

UL File No.: E36332

UL Category Control No.: NLRV

VDE 0660

CSA-C22.2 No. 94

UL 60947-4-1

CE

CSA File No.: 012528

UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 018947 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing materia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-2/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.