

INDUSTRIAL COMPONENT DATA

T3-3-2/XZ 018950 Y7-18950 EATON ELECTRIC Reversing switches, Contacts: 5, 32 A, 45 °, rear mounting, Basic s..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-2/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-2/XZ
Catalog number	Y7-18950
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-87E7CC2CF4
Generated	2026-08-05

Product Overview

Reversing switches, Contacts: 5, 32 A, 45 °, rear mounting, Basic switch

Reversing switch; 5-pole; 32; 45 °; Mounting bottom panel; Switch replacement part for case

Reversing switches, T3, 32 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 5, 45 °, design no. 2

Reversing switch, Product range: Control switches, Part group reference: T3, Contacts: 5, Design: rear mounting, Basic switch, Switching angle: 45 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Reversing switches, T3, 32 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 5, 45 °, design no. 2Reversing switch, Product range: Control switches, Part group reference: T3, Contacts: 5, Design: rear mounting, Basic switch, Switching angle: 45 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT3Basic functionReversing switchesContacts5Designrear mounting Basic switchContact sequenceSwitching angle45 °Design number2Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [I_u]32 ANote on rated uninterrupted current !uRated uninterrupted current I_{uis} specified for max. cross-section.Number of contact units3 contact unit(s)Technical data GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40
°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock
resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V
ACElectrical characteristicsRated uninterrupted current [Iu]32 AElectrical characteristicsNote on rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-2/XZ with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.