

INDUSTRIAL COMPONENT DATA

T3-3-6/E 019353 Y7-19353 EATON ELECTRIC Multi-speed switches, Contacts: 6, 32 A, 2 speeds, 2 separate windin..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-6/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-6/E
Catalog number	Y7-19353
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-26C919B84D
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 6, 32 A, 2 speeds, 2 separate windings, front plate: 0-2, 60 °, maintained, flush mounting
Switch Multi-speed; 6-pole; 32; 2 speeds; 2 separate windings; rating Plate: 0-2; 60 °; Interlock; recessed Mounting
Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, flush mounting, 3 contact unit(s), Contacts: 6, 60 °, maintained,
With 0 (Off) position, 0-2, Design number 6

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate,
Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 separate windings,
Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-2, Motor rating AC-23A, 50 -
60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660,
IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 019353 Model Code T3-3-6/E EAN
4015080193531 Product Length/Depth 102 mm Product Height 54 mm Product Width 61 mm Product Weight 0.21 kg

Certifications CSA File No.: 012528

UL 60947-4-1

CSA Class No.: 3211-05

VDE 0660

CSA

UL

UL File No.: E36332

IEC/EN 60204

CE

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

IEC/EN 60947

IEC/EN 60947-3

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 019353 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-6/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.