

INDUSTRIAL COMPONENT DATA

T3-3-7/I2 222874 Y7-222874 EATON ELECTRIC Multi-speed switches, Contacts: 6, 32 A, 2 speeds, 2 separate wind..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-7/I2



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-7/I2
Catalog number	Y7-222874
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-4539FA7D0A
Generated	2026-08-06

Product Overview

Multi-speed switches, Contacts: 6, 32 A, 2 speeds, 2 separate windings, front plate: 2-0-1, 60 °, maintained, surface mounting

T3-3-7/I2

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, surface mounting, 3 contact unit(s), Contacts: 6, 60 °, maintained, With 0 (Off) position, 2-0-1, Design number 7

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 222874 Model Code T3-3-7/I2 EAN

4015082228743 Product Length/Depth 181 mm Product Height 127 mm Product Width 100 mm Product Weight 0.563 kg

Certifications CSA

IEC/EN 60204

CSA Class No.: 3211-07

UL
UL Category Control No.: NLRV
CE
CSA File No.: 012528
CSA-C22.2 No. 94
IEC/EN 60947
UL 60947-4-1
CSA-C22.2 No. 60947-4-1-14
IEC/EN 60947-3
UL File No.: E36332
VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 222874 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Pole switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current I_u (EF001389)
32 A
Rated operation current I_e at AC-3, 400 V (EF001392)
23.7 A
Rated operation power at AC-3, 400 V (EF001364)
12 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)

Yes

Housing materia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-7/I2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.