

INDUSTRIAL COMPONENT DATA

T3-4-11/E 020044 Y7-20044 EATON ELECTRIC Multi-speed switches, Contacts: 8, 32 A, One tapped winding, 2 spee..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-11/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-11/E
Catalog number	Y7-20044
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-4D035AB8A9
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 8, 32 A, One tapped winding, 2 speeds, front plate: 1-2, 90 °, maintained, flush mounting
Switch Multi-speed; 8-pole; 32; 1 winding threading; 2 speeds; rating Plate: 1-2; 90 °; Latch; flush Mount
Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, flush mounting, 4 contact unit(s), Contacts: 8, 90 °, maintained,
Without 0 (Off) position, 1-2, Design number 11

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate,
Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds,
Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50
- 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660,
IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 020044 Model Code T3-4-11/E EAN
4015080200444 Product Length/Depth 114 mm Product Height 54 mm Product Width 61 mm Product Weight 0.252 kg

Certifications UL Category Control No.: NLRV

IEC/EN 60204

VDE 0660

CE

CSA-C22.2 No. 60947-4-1-14

UL

UL 60947-4-1

UL File No.: E36332

CSA Class No.: 3211-05

CSA-C22.2 No. 94

CSA File No.: 012528

IEC/EN 60947-3

IEC/EN 60947

CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 020044 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing materi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-11/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.