

INDUSTRIAL COMPONENT DATA

T3-4-15056/XZ 020100 Y7-20100 EATON ELECTRIC Step switch, 2p, Ie 25A, 1-4, 90°, maintained, replacement swit..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-15056/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-15056/XZ
Catalog number	Y7-20100
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-F2515FCCBA
Generated	2026-08-05

Product Overview

Step switch, 2p, Ie=25A, 1-4, 90°, maintained, replacement switch, base fixing
Switch steps; 2p; 25A; 1-4; 90°; Latch; Switch replacement part for case
T3, 32 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 90 °, design no. 15056
Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 8, Design: rear mounting, Basic switch, Switching angle: 90 °, 4 contact unit(s), Rated uninterrupted current: Iu= 32 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

T3, 32 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 90 °, design no. 15056
Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 8, Design: rear mounting, Basic switch, Switching angle: 90 °, 4 contact unit(s), Rated uninterrupted current: Iu= 32 A
Delivery program
Product rangeControl switchesPart group referenceT3Contacts8Designrear mounting
Basic switchContact sequenceSwitching angle90 °Design number15056Front plate no.Motor rating AC-23A, 50 - 60 Hz
[P]400 V [P]15 kWRated uninterrupted current [Iu]32 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units4 contact unit(s)Technical data
GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40 °C
Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V AC
Electrical characteristics Rated uninterrupted current [Iu] 32 A Electrical characteristics Note on rated uninterrupted current Iu
Rated uninterrupted current Iu is specified for max. cross-section. Load rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-15056/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.