

INDUSTRIAL COMPONENT DATA

T3-4-15164/I2/SVB-SW 222901 Y7-222901 EATON ELECTRIC

Main switch, 6 pole + 1 N/O + 1 N/C, 32 A, STOP functio..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-15164/I2/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-15164/I2/SVB-SW
Catalog number	Y7-222901
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-1F51E4E063
Generated	2026-08-04

Product Overview

Main switch, 6 pole + 1 N/O + 1 N/C, 32 A, STOP function, 90 °, surface mounting

T3-4-15164/I2/SVB-SW

Eaton Moeller® series T3 Main switch, T3, 32 A, surface mounting, 4 contact unit(s), 6 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: STOP function, With black rotary handle and locking ring, 6 pole, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Main switch Catalog Number 222901 Model Code T3-4-15164/I2/SVB-SW EAN 4015082229016 Product Length/Depth 181 mm Product Height 135 mm Product Width 100 mm Product Weight 0.628 kg

Compliances CE Marked Certifications EN 60947-3

IEC 60947

UL 508

CSA Std. C22.2 No. 14-05

VDE

CSA
UL
CE
CSA File No.: 012528
CSA-C22.2 No. 94
IEC/EN 60947
VDE 0660
IEC/EN 60204
IEC/EN 60947-3
UL 60947-4-1
CSA-C22.2 No. 60947-4-1-14
UL File No.: E36332
CSA Class No.: 3211-07
UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 222901 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
32 A
Rated permanent current at AC-23, 400 V (EF011777)
32 A
Rated permanent current at AC-21, 400 V (EF009165)
32 A
Rated operation power at AC-3, 400 V (EF001364)
11 kW
Rated short-time withstand current I_{cw} (EF007050)
0.65 kA
Rated operation power at AC-23, 400 V (EF007027)
15 kW
Switching power at 400 V (EF009166)
15 kW
Conditioned rated short-circuit current I_q (EF001444)
1 kA

Number of poles (EF001391)

6

Number of auxiliary cont...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-15164/I2/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.