

INDUSTRIAL COMPONENT DATA

T3-4-4/I2 222907 Y7-222907 EATON ELECTRIC Multi-speed switches, Contacts: 8, 32 A, One tapped winding, 2 spe..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-4/I2



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-4/I2
Catalog number	Y7-222907
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F507B710DF
Generated	2026-08-06

Product Overview

Multi-speed switches, Contacts: 8, 32 A, One tapped winding, 2 speeds, front plate: 0-1-2, 60 °, maintained, surface mounting

T3-4-4/I2

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, surface mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 0-1-2, Design number 4

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 222907 Model Code T3-4-4/I2 EAN

4015082229078 Product Length/Depth 181 mm Product Height 127 mm Product Width 100 mm Product Weight 0.594 kg

Compliances CE Marked Certifications UL 508

EN 60947-3

CSA Std. C22.2 No. 14-05

IEC 60947
VDE
UL Category Control No.: NLRV
UL 60947-4-1
IEC/EN 60947
VDE 0660
IEC/EN 60204
IEC/EN 60947-3
CSA-C22.2 No. 94
CSA
UL File No.: E36332
CSA-C22.2 No. 60947-4-1-14
CE
CSA File No.: 012528
CSA Class No.: 3211-07
UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 222907 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Dahlander switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current I_u (EF001389)
32 A
Rated operation current I_e at AC-3, 400 V (EF001392)
23.7 A
Rated operation power at AC-3, 400 V (EF001364)
12 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No

Suitable for distribution board installation (EF007262)

No

Suitable for intermedi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-4/I2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.